

APPLICATION UNDER UNITED STATES PATENT LAWS

Atty. Dkt. No. PW 283277
(M#)

Invention: RADIATION-CURABLE COMPOSITION AND PRODUCTS COATED THEREWITH

Inventor (s): Timothy Edward BISHOP
Jibing LIN
David KRUMIN
Lindsay Scott COONS
Paulus Franciscus Anna BUIJSEN



00909

Pillsbury Winthrop LLP

This is a:

- ☐ Provisional Application
- ☒ Regular Utility Application
- ☐ Continuing Application
 - ☒ The contents of the parent are incorporated by reference
- ☐ PCT National Phase Application
- ☐ Design Application
- ☐ Reissue Application
- ☐ Plant Application
- ☐ Substitute Specification
 - Sub. Spec Filed _____
 - in App. No. _____ / _____
- ☐ Marked up Specification re
 - Sub. Spec. filed _____
 - In App. No. _____ / _____

SPECIFICATION

RADIATION-CURABLE COMPOSITION AND PRODUCTS COATED THEREWITH

Field of the Invention

The present invention relates to radiation-curable compositions. The invention
5 further relates to products coated with these compositions.

Background of the Invention

Radiation-curable compositions have been used to provide coatings for optical
fibers. Optical fibers are generally coated with two superposed radiation-cured
10 coatings, which together form a primary coating. The coating which is in direct contact
with the glass is called the inner primary coating and the overlaying coating(s) is called
the outer primary coating.

The inner primary coating is usually a relatively soft coating providing
environmental protection to the glass fiber and resistance, inter alia, to the well-known
15 phenomenon of microbending. Microbending in the coated fiber can lead to attenuation
of the signal transmission capability of the coated fiber and is therefore undesirable.
The outer primary coating(s), which is on the exposed surface of the coated fiber, is
typically a relatively harder coating designed to provide a desired resistance to physical
handling forces, such as those encountered when the fiber is cabled.

20 Inner primary radiation-curable compositions typically comprise a radiation-
curable oligomer and a reactive diluent. The oligomer has a relatively high molecular
weight, which allows for a certain integrity and toughness of the composition when
cured, but which also, in conventional compositions, raises the viscosity of the
compositions to a level that is unacceptable in fiber coating processes. Accordingly,
25 substantial amounts of reactive diluent are added to bring the viscosity down to
acceptable levels.

However, a drawback of reactive diluents is that they can increase the glass
transition temperature of inner primary coatings, often resulting in an undesirable
increase of the tensile modulus, in particular at low temperatures. This increase in
30 modulus can result in attenuation of the signal transmission capability of the optical
fiber.

A further drawback of the relatively low molecular weight reactive diluents is the
release of volatile components during coating processes. Accordingly, it is an object
of the present invention to provide a radiation-curable composition comprising a low

amount of reactive diluents while still exhibiting a sufficiently low viscosity for coating applications.

Another aspect of the invention is providing a radiation curable composition comprising a low amount of reactive diluents and exhibiting, after cure, a low glass
5 transition temperature.

Summary of the Invention

The present invention provides radiation curable compositions comprising an oligomer and, relative to the total weight of the composition, less than 20 wt%
10 monofunctional reactive diluents, while still exhibiting a viscosity of less than 10,000 cps at 25 °C and a secant modulus after cure of less than 5 MPa. The invention further provides articles, such as optical fibers, having a coating obtained by curing these compositions.

In addition, the present invention provides compositions comprising an oligomer
15 and, relative to the total weight of the composition, less than 45 wt% reactive diluents, wherein at least 50 mole% of the diisocyanates used to prepare the oligomer are absent of a ring structure, and wherein the composition has a viscosity of less than 10,000 cps at 25 °C.

20 Detailed Description of Preferred Embodiments

"Aliphatic" refers in this application to being exclusive of an aromatic ring.

"Reactive diluent" refers in this application to radiation-curable compounds having a molecular weight below 1,500 g/mol.


"Silicone oligomer" refers in this application to a compound comprising silicon
25 atoms and having a molecular weight of more than 1,500 g/mol.

(A) Oligomers

Compositions according to the present invention comprise a radiation curable oligomer. The compositions of the present invention may comprise any suitable amount
30 of oligomer, such as, for instance, 40 wt.% to 99 wt.%, and typically the amount of oligomer in the compositions is at least 50 wt%, preferably at least 65 wt%, more preferably at least 75 wt%, and most preferably at least 85 wt%, all said weight percentages being relative to the total weight of the composition. If more than one oligomer is present, then the wt.% of each oligomer is added.

35 Radiation-curable oligomers can comprise one or more radiation-curable end groups and an oligomer backbone. The end-group provides a cure mechanism,

whereas the backbone provides suitable mechanical properties upon cure. In addition, the oligomer can comprise one or more linking groups such as a urethane- or urea-containing moiety which further can improve the mechanical performance of cured compositions. The linking groups can link an oligomeric backbone moiety to the radiation-curable end-group, or link oligomeric backbone moieties to themselves. Hence, for example, radiation-curable oligomers can be prepared from three basic components (backbone, linking, and radiation-curable components) and can be represented by structures such as, for example:



where R is a radiation-curable group, L is a linking group, and B is a backbone moiety. The variable x indicates the number of backbone moieties per oligomer molecule. This value X can be controlled by, for example, control of the reaction stoichiometry during oligomer synthesis. Typically, X is designed to be 1 or 2. In this representation, L and B are difunctional moieties, but oligomers can also be prepared from tri- and higher functional L and B moieties to provide branching.

In particular, typical radiation-curable urethane acrylate oligomers according to the present invention are prepared from (i) at least one ingredient which reacts to provide the radiation-curable acrylate group R, (ii) at least one ingredient which reacts to provide the urethane linking group L, and (iii) at least one ingredient which reacts to provide the backbone B. Different urethane acrylate oligomer synthetic strategies are disclosed in, for example, U.S. Patent No. 5,093,386, which is hereby incorporated by reference. Other synthetic methods, however, may be used to prepare equivalent structures. These methods may be adapted by methods known in the art to provide urea linkages, methacrylate linkages, and other common types of linkages found in radiation-curable oligomers.

The radiation-curable oligomer can cure by reaction of its radiation-curable groups, R, via a free-radical mechanism or by cationic mechanism. A free-radical cure, however, is preferred. Ethylenically unsaturated groups are preferred. Exemplary radiation-curable groups include (meth)acrylate, vinyl ether, vinyl, acrylamide, maleate, fumarate, and the like. The radiation-curable vinyl group can participate in thiol-ene or amine-ene cure. Most preferably, the radiation-curable group is an acrylate if fast cure speed is desired.

Preferably, the oligomer comprises at least two radiation-curable groups, and preferably, at least two ethylenically unsaturated groups. The oligomer, for example, can comprise two, three, or four radiation-curable groups which are all preferably ethylenically unsaturated groups. There is no strict upper limit on the number of

radiation-curable groups per oligomer, but in general, the number of radiation-curable groups is less than 10, and preferably, less than 8.

The oligomer can comprise copolymeric structures including random and block copolymeric structures. Methods known in the art can be used to prepare such
5 copolymeric structures. For example, backbone moieties can be copolymeric. Also, a one-pot synthesis of multiple oligomers can be executed with use of multiple backbone moieties. Using multiple backbone moieties can yield at least some block copolymeric oligomers in the pre-polymer system. Formulation design of copolymeric oligomers can result in a better balance of properties and provide synergistic effects, which usually is
10 crucial for fiber optic materials. In addition, oligomer blends or mixtures can be used to balance properties and provide synergistic effects.

For processing reasons, it is important to control the oligomer system's viscosity and flow behavior. For practical reasons, oligomers should be easy to remove from the reactors and flasks in which they are synthesized. If viscosity is too high, it will be
15 difficult to process the oligomer system during formulation, even with some monomer diluent present.

If an oligomeric polyether diol is used, the polyether may include, for example, substantially non-crystalline polyethers. The oligomer may include polyethers comprising repeating units of one or more of the following monomer units:

20 -O-CH₂-CH₂-
-O-CH₂-CH₂-CH₂-
-O-CH₂-CH(CH₃)-
-O-CH₂-CH₂-CH₂-CH₂-
-O-CH₂-CH(CH₃)-CH₂-
25 -O-CH₂-CH(CH₃)₃-CH₂-CH₂-
-O-CH(CH₃)-CH₂-CH₂-CH₂-
-O-CH(CH₂CH₃)-CH₂-
-O-CH₂-C(CH₃)(CH₃)- , and the like.

An example of a polyether polyol that can be used is the polymerization product
30 of (i) tetrahydrofuran, or (ii) a mixture of 20 percent by weight of 3-methyltetrahydrofuran and 80 percent by weight of tetrahydrofuran, both of which have undergone a ring opening polymerization. This latter polyether copolymer contains both branched and non-branched oxyalkylene repeating units and is marketed as PTGL 1000 (Hodogaya Chemical Company of Japan). Another example of a polyether in this
35 series which can be used is PTGL 2000 (Hodogaya Chemical Company). Butyleneoxy

repeat units are preferred to impart flexibility to one oligomer in particular and the pre-polymer system in general. Particularly preferred are ethyleneoxy-butyleneoxy (EBO) copolymers because they tend to have a relatively low viscosity compared to other polymers of comparable molecular weight.

- 5 If a polyolefin diol is used, the polyolefin is preferably a linear or branched hydrocarbon containing a plurality of hydroxyl end groups. Fully saturated, for example, hydrogenated hydrocarbons, are preferred because the long term stability of the cured coating increases as the degree of unsaturation decreases. Examples of hydrocarbon diols include, for example, hydroxyl-terminated, fully or partially hydrogenated 1,2-
10 polybutadiene; 1,4- and 1,2-polybutadiene copolymers, 1,2-polybutadiene-ethylene or -propylene copolymers, polyisobutylene polyol; mixtures thereof, and the like.

- Other suitable oligomers include, for instance, polyester oligomers, polycarbonate oligomers, acrylic oligomers, mixtures of any of the aforementioned oligomer types and the like. Preferably the oligomers used in the present invention are
15 not silicone oligomers, and when a silicone oligomer is nevertheless used it is always in conjunction with at least one non-silicone oligomer present in a higher amount than said silicone oligomer. Preferably the present compositions comprise, relative to the total weight of the composition, less than 10 wt% of silicone oligomer, more preferably less than 5 wt%, and most preferably 0 wt%.

- 20 The linking group of the oligomer can be any suitable group, such as a urethane or urea group, and preferably is a urethane group. It is well-known in the art that urethane linkages can be formed by reaction of a polyfunctional isocyanate with a hydroxy compound including a hydroxy-containing backbone component or a hydroxy-containing radiation-curable component.

- 25 Polyfunctional isocyanates include diisocyanates, triisocyanates, and higher order polyisocyanates which can provide the linking group. As known in the art, isocyanate compounds can be trimerized to form isocyanurate compounds which can provide the linking group. Hence, polyisocyanate compounds can be oligomerized or polymerized to form higher order polyisocyanates comprising isocyanurate group. In
30 the preparation of an oligomer, it is preferred that at least 50 mole% of the diisocyanates used are exclusive of a ring structure, preferably at least 65 mole%, more preferably at least 75 mole%, and most preferably 100 mole% of the diisocyanates used are non-cyclic. The absence of a cyclic structure can aid in increasing cure speed, lowering viscosity, and/or lowering the glass transition
35 temperature. Examples of non-cyclic diisocyanates include, for instance, tetramethylene diisocyanate, 2,2,4 trimethyl-1,6-diisocyanate-hexane, and

hexamethylene diisocyanate. Examples of cyclic diisocyanates include, for instance, toluenediisocyanate (TDI), isophoronediiisocyanate (IPDI), diphenylmethane diisocyanate, hydrogenated diphenylmethane diisocyanate, and methylenebis(4-cyclohexylisocyanate).

- 5 Generally, the compound providing a radiation-curable terminus to the oligomer contains a functional group which can polymerize under the influence of actinic radiation and a functional group which can react with the diisocyanate. Hydroxy functional ethylenically unsaturated monomers are preferred. More preferably, the hydroxy functional ethylenically unsaturated monomer contains acrylate, methacrylate, 10 vinyl ether, maleate or fumarate functionality.

- In the reaction between hydroxy group of the compound providing the terminus and isocyanate groups of compound providing the linking sites, it is preferred to employ a stoichiometric balance between hydroxy and isocyanate functionality and to preferably maintain the reaction temperature of at least 25°C. The hydroxy 15 functionality should be substantially consumed. The hydroxy functional ethylenically unsaturated monomer attaches to the isocyanate via a urethane linkage. Monomers having (meth)acrylate functional groups include, for example, hydroxy functional (meth)acrylates such as 2-hydroxyethyl acrylate, 2-hydroxypropyl acrylate, caprolactone acrylate (e.g. SR495 from Sartomer), methacrylate analogs, and the like. 20 Monomers having vinyl ether functional groups include, for example, 4-hydroxybutyl vinyl ether, and triethylene glycol monovinyl ether. Monomers having maleate functional groups include, for example, maleic acid and hydroxy functional maleates.

- There is no particular limitation on the molecular weight of the oligomer, but the number average molecular weight of the oligomer in general can be less than about 25,000 g/mol, and preferably, less than about 10,000 g/mol, and more preferably, less 25 than about 7,000 g/mol. The molecular weight is greater than 1,500 g/mol, preferably greater than 2,000 g/mol, more preferably greater than 3,000 g/mol, and most preferably the molecular weight is 3,000-6,000 g/mol.

30 (B) Reactive Diluents

- Although the amount is preferably kept low, the composition may comprise reactive diluents. Preferably the composition comprises less than 25 wt%, relative to the total weight of the composition, more preferably less than 10 wt%, even more preferably less than 5 wt%, and most preferably about 0 wt% of monofunctional 35 diluents. The composition generally comprises less than 45 wt%, relative to the total weight of the composition, of monofunctional and polyfunctional diluents combined,

preferably less than 20 wt%, more preferably less than 10 wt%, even more preferably less than 5 wt%, and most preferably less than 2.5 wt%.

The radiation-curable functional group present on the reactive diluent may be of the same nature as that used in the radiation-curable oligomer. Preferably, the radiation-curable functional group present in the reactive diluent is capable of copolymerizing with the radiation-curable functional group present on the radiation-curable oligomer. Ethylenic unsaturation is preferred. In particular, acrylate unsaturation is preferred.

The reactive diluent system may comprise a monofunctional monomer having an acrylate or vinyl ether functionality and an C₄-C₂₀ alkyl or polyether moiety. Examples of such reactive diluents include hexylacrylate, 2-ethylhexylacrylate, isobornylacrylate, decylacrylate, laurylacrylate, stearylacrylate, ethoxyethoxyethylacrylate, laurylvinylether, 2-ethylhexylvinyl ether, N-vinyl formamide, isodecyl acrylate, isooctyl acrylate, vinyl-caprolactam, N-vinylpyrrolidone and the like.

Another type of monofunctional reactive diluents are monofunctional compound comprising an aromatic group. Examples of monofunctional diluents having an aromatic group include: ethyleneglycolphenyletheracrylate, polyethyleneglycolphenyletheracrylate, polypropyleneglycolphenyletheracrylate, and alkyl-substituted phenyl derivatives of the above monomers, such as polyethyleneglycolnonylphenyletheracrylate.

If monofunctional reactive diluents are present, preferably at least 50 wt%, relative to the total weight of monofunctional reactive diluents, more preferably at least 75 wt%, and most preferably 100 wt% of the monofunctional reactive diluents is absent an aromatic ring.

Furthermore, a reactive diluent may be polyfunctional, for instance it may contain two groups capable of polymerization using actinic radiation. A diluent having three or more of such reactive groups can be present as well. Examples of such monomers include: C₂-C₁₈ hydrocarbodioldiacrylates, C₄-C₁₈ hydrocarbodivinylethers, C₃-C₁₈ hydrocarbontrioletriacylates, the polyether analogs thereof, and the like, such as

- 1,6-hexanedioldiacrylate,
trimethylolpropanetriacrylate,
hexanedioldivinylether,
triethyleneglycoldiacrylate,
5 pentaeritritoltriacrylate,
tripropylene glycol diacrylate, and
alkoxylated bisphenol A diacrylate.

Particularly preferred diluents, when used, are alkoxylated diluents that are
10 exclusive of an aromatic ring, such as ethoxylated or propoxylated lauryl acrylate and
isodecyl acrylate. An advantage of alkoxylated aliphatic diluents is that they can
increase the cure speed of the radiation-curable composition.

(C) Photoinitiators

- 15 The composition may optionally further comprise at least one photoinitiator.
Photoinitiators are generally required for a fast UV cure but may be omitted for electron
beam cure. Conventional photoinitiators can be used. Examples include
benzophenones, acetophenone derivatives, such as alpha-hydroxyalkylphenylketones,
benzoin alkyl ethers and benzil ketals, monoacylphosphine oxides, and
20 bisacylphosphine oxides. A preferred photoinitiator is 1-hydroxycyclohexylphenylketone
(Irgacure 184, Ciba Geigy).

Often mixtures of photoinitiators provide a suitable balance of properties. The
amount of photoinitiator system is not particularly limited but will be effective to provide
fast cure speed, reasonable cost, good surface and through cure, and lack of yellowing
25 upon aging. Typical amounts can be, for example, about 0.3 wt.% to about 10 wt.%,
preferably about 1 wt.% to about 6 wt.%.

(D) Additives

- The composition may further comprise additives, such as, for instance, UV
30 absorbers, chain transfer agents, inorganic fillers, antioxidants (e.g. Irganox 1035
available from Ciba Geigy), or silane adhesion promoters, e.g. mercapto functional
silane adhesion promoters such as gamma-mercaptopropyltrimethoxy silane.

(E) Properties

- 35 The viscosity of the composition is preferably less than 10,000 cps at 25 °C,
more preferably less than 7,000 cps, and most preferably less than 6,000 cps. It is

further preferred that the composition has a viscosity of less than 3,000 cps, preferably 1,000-3,000 cps, in at least part of the range 40°C-60°C. Preferably the composition has a viscosity of less than 3,000 cps, preferably 1,000-3,000 cps, in the entire range of 40°C-60°C.

- 5 The composition, after radiation cure, preferably has an elongation at break of at least 75%, more preferably at least 100%, most preferably about 100-200%. The secant modulus of the composition, after cure, is preferably less than 5 MPa, more preferably less than 3 MPa, even more preferably less than 1.5 MPa, and most preferably about 0.1-1.3 MPa. The glass transition temperature of the composition,
10 after cure, is preferably less than -20°C, preferably less than -30°C, more preferably less than -40°C, and most preferably less than -50°C.

- The cure speed of the present compositions, defined as the UV dose required to reach 95% of the maximum attainable modulus of a 75µm thick layer of the composition generally will be less than 0.7 J/cm², is preferably less than 0.35 J/cm²,
15 more preferably less than 0.25 J/cm², and most preferably less than 0.15 J/cm².

 The compositions of the present invention are useful in a wide variety of applications, such as in coating applications. The compositions are, for example, useful as coatings for optical fibers, e.g. as inner primary coatings.

20 Examples

 The following examples are given as particular embodiments of the invention and to demonstrate the practice and advantages thereof. It is to be understood that the examples are given by way of illustration and are not intended to limit the specification or the claims that follow in any manner.

25

 Three composition (indicated as Example I, II, and III) were prepared with the ingredients listed in Table I. The amounts of the ingredients listed in Table I are in weight percentage relative to the total weight of the composition.

30

35

Table I

Ingredient	Example I	Example II	Example III
H-TMDI-PPG2000-TDI-PTGL2000-TMDI-H	53.6	--	--
H-TMDI-PPG2000-TDI-EOBO2000-TMDI-H	--	69.00	--
H-TMDI-EOBO4000-TMDI-H	--	--	88.90
Ethoxylated lauryl acrylate	33.30	17.70	--
Vinyl Caprolactam	5.00	5.00	5.00
Bisphenol A ethoxylated diacrylate	2.10	2.20	0.10
Tinuvin 622	0.10	0.10	0.10
gamma-mercaptopropyl trimethoxysilane	0.9	0.9	0.9
Irgacure 1700	3.00	3.00	3.00
Irgacure 184	2.00	2.00	2.00
Test data:			
Viscosity (cps, 25°C)	4,900	5,300	6,000
Glass transition temperature (°C)	-40	-53	-61
Secant Modulus (MPa)	1.04	1.14	1.07
Elongation (%)	147	107	121
Cure Speed (J/cm ² required to reach 95% of maximum attainable modulus)	0.28	0.19	0.08

H = Hydroxyethylacrylate residue;

TMDI = 2,2,4-trimethylene-1,6-diisocyanate-hexane residue;

5 TDI = Toluenediisocyanate residue;

PPG2000 = polypropylene glycol residue having a molecular weight of about 2,000;

PTGL2000 = polymethyltetrahydrofurfuryl-polytetrahydrofurfuryl copolymer diol residue having a molecular weight of about 2,000;

EOBO2000 = is an ethyleneoxide-butyleneoxide copolymer residue having a molecular weight of about 2,000;

10 EOBO4000 = is an ethyleneoxide-butyleneoxide copolymer residue having a molecular weight of about 4,000;

Irgacure 1700 = a photoinitiator available from Ciba Geigy;

Irgacure 184 = a photoinitiator available from Ciba Geigy;

Tinuvin 622 = UV absorber

- 5 Four further compositions (indicated as Examples IV-VII) were prepared with the ingredients listed in Tables II and III. The amounts of the ingredients listed in Tables II and III are in weight percentage relative to the total weight of the composition. Results are also given in these tables.

Table II:

Ingredient	Example IV	Example V
H-TMDI-Acclaim4200-TMDI-H	88.9	--
H-TMDI-EOBO4000 -TMDI-H	--	91.0
Vinyl Caprolactam	5.0	--
Bisphenol A ethoxylated diacrylate (SR349D from Sartomer)	0.1	--
Hexane Diol Diacrylate	--	3.0
Irgacure 1700	3.0	3.0
Irgacure 184	2.0	2.0
Gamma-mercaptopropyl trimethoxysilane	0.9	0.9
Tinuvin 622 LD	0.1	0.1
Test data:		
Viscosity (cps, 25°C)	6,792	6,387
Glass transition temperature (°C)	-57	-62
Secant Modulus (MPa)	1.557	1.091
Elongation (%)	78.6	93.6
Cure speed (J/cm ²)	0.11	0.23

Acclaim 4200 = a polypropylene glycol residue having a molecular weight of about 4200.

Table III:

Ingredient	Example VI	Example VII
H-I-EOBO4000-I-H	92.5	--
H-TMDI-Acclaim4200-TMDI-H	--	92.5
Isodecyl Acrylate	5.0	5.0
Chivacure TPO	1.0	1.0
Chivacure 184	0.5	0.5
Gamma-mercaptopropyl trimethoxysilane	0.9	0.9
Tinuvin 622 LD	0.1	0.1
Test data:		
Viscosity (cps, 25°C)	8,263	6,500
Glass transition temperature (°C)	< -50°C	< -60°C
Secant Modulus (MPa)	1.306	1.08
Elongation (%)	73.1	94.6
Cure speed (J/cm ²)	0.68	0.36

Chivacure TPO = photoinitiator

Chivacure 184 = photoinitiator

Test Methods:

5 Viscosity Test Method

The viscosity was measured using a Physica MC10 Viscometer. The test samples were examined and if an excessive amount of bubbles was present, steps were taken to remove most of the bubbles. Not all bubbles need to be removed at this stage, because the act of sample loading introduces some bubbles.

- 10 The instrument was set up for the conventional Z3 system, which was used. The samples were loaded into a disposable aluminum cup by using the syringe to measure out 17 cc. The sample in the cup was examined and if it contains an excessive amount of bubbles, they were removed by a direct means such as centrifugation, or enough time was allowed to elapse to let the bubbles escape from the
- 15 bulk of the liquid. Bubbles at the top surface of the liquid are acceptable.

The bob was gently lowered into the liquid in the measuring cup, and the cup and bob were installed in the instrument. The sample temperature was allowed to equilibrate with the temperature of the circulating liquid by waiting five minutes. Then, the rotational speed was set to a desired value which will produce the desired shear

rate. The desired value of the shear rate is easily determined by one of ordinary skill in the art from an expected viscosity range of the sample.

The instrument panel read out a viscosity value, and if the viscosity value varied only slightly (less than 2% relative variation) for 15 seconds, the measurement was complete. If not, it is possible that the temperature had not yet reached an equilibrium value, or that the material was changing due to shearing. If the latter case, further testing at different shear rates will be needed to define the sample's viscous properties. The results reported are the average viscosity values of three test samples.

10 Tensile Strength, Elongation and Modulus Test Method

The tensile strength, elongation and secant modulus of cured samples was tested using a universal testing instrument, Instron Model 4201 equipped with a personal computer and software "Series IX Materials Testing System." The load cells used were 2 and 20 pound capacity. The ASTM D638M was followed, with the following modifications.

A drawdown of each material to be tested was made on glass plate or Mylar (in particular, the outer primary coating compositions, unless otherwise noted, were measured on Mylar) and cured using a UV processor. The cured film was conditioned at 22 to 24°C and 50 \pm 5% relative humidity for a minimum of sixteen hours prior to testing.

A minimum of eight test specimens, having a width of .5 \pm 0.002 inches and a length of 5 inches, were cut from the cured film. To minimize the effects of minor sample defects, sample specimens were cut parallel to the direction in which the drawdown of the cured film was prepared. If the cured film was tacky to the touch, a small amount of talc was applied to the film surface using a cotton-tipped applicator.

The test specimens were then removed from the substrate. Caution was exercised so that the test specimens were not stretched past their elastic limit during the removal from the substrate. If any noticeable change in sample length had taken place during removal from the substrate, the test specimen was discarded.

If the top surface of the film was talc coated to eliminate tackiness, then a small amount of talc was applied to the bottom surface of test specimen after removal from the substrate.

The average film thickness of the test specimens was determined. At least five measurements of film thickness were made in the area to be tested (from top to bottom) and the average value used for calculations. If any of the measured values of film thickness deviates from the average by more than 10% relative, the test specimen

was discarded. All specimens came from the same plate.

The appropriate load cell was determined by using the following equation:

$$[A \times 145] \times 0.0015 = C$$

5 Where: A = Product's maximum expected tensile strength (MPa);

145 = Conversion Factor from MPa to psi;

0.00015 = approximate cross-sectional area (in²) of
test specimens; and

C = lbs.

10 The 2 pound load cell was used for materials where C=1.8 lbs. The 20 pound
load cell was used for materials where $1.8 < C < 18$ lbs. If $C > 19$, a higher capacity
load cell was required.

The crosshead speed was set to 1.00 inch/min (25.4 mm/min), and the
crosshead action was set to "return at break". The crosshead was adjusted to 2.00
15 inches (50.8 mm) jaw separation. The air pressure for the pneumatic grips was turned
on and adjusted as follows: set approximately 20 psi (1.5 Kg/cm²) for primary optical
fiber coatings and other very soft coatings; set approximately 40 psi (3Kg/cm²) for
optical fiber single coats; and set approximately 60 psi (4.5 Kg/cm²) for secondary
optical fiber coatings and other hard coatings. The appropriate Instron computer
20 method was loaded for the coating to be analyzed.

After the Instron test instrument had been allowed to warm-up for fifteen
minutes, it was calibrated and balanced following the manufacturer's operating
procedures.

25 The temperature near the Instron Instrument was measured and the humidity
was measured at the location of the humidity gage. This was done just before
beginning measurement of the first test specimen.

Specimens were only analyzed if the temperature was within the range $23 \pm$
1.0°C and the relative humidity was within $50 \pm 5\%$. The temperature was verified as
being within this range for each test specimen. The humidity value was verified only at
30 the beginning and the end of testing a set of specimens from one plate.

Each test specimen was tested by suspending it into the space between the
upper pneumatic grips such that the test specimen was centered laterally and hanging
vertically. Only the upper grip was locked. The lower end of the test specimen was
pulled gently so that it has no slack or buckling, and it was centered laterally in the

space between the open lower grips. While holding the specimen in this position, the lower grip was locked.

The sample number was entered and sample dimensions into the data system, following the instructions provided by the software package.

5 The temperature and humidity were measured after the last test specimen from the current drawdown was tested. The calculation of tensile properties was performed automatically by the software package.

10 The values for tensile strength, % elongation, and secant modulus were checked to determine whether any one of them deviated from the average enough to be an "outlier." If the modulus value was an outlier, it was discarded. If there were less than six data values for the tensile strength, then the entire data set was discarded and repeated using a new plate.

Dynamic Mechanical Testing

15 The elastic modulus (E'), the viscous modulus (E''), and the tan delta (E''/E'), which is an indication of the material's T_g , of the examples were measured using a Rheometrics Solids Analyzer (RSA-11), equipped with: 1) a personal computer having MS-DOS 5.0 operating system and having Rhios[®] software (Version 4.2.2 or later) loaded, and 2) a liquid nitrogen controller system for low-temperature operation.

20 The test samples were prepared by casting a film of the material, having a thickness in the range of 0.02 mm to 0.4 mm, on a glass plate. The sample film was cured using a UV processor. A specimen approximately 35 mm (1.4 inches) long and approximately 12 mm wide was cut from a defect-free region of the cured film. For soft films, which tend to have sticky surfaces, a cotton-tipped applicator was used to coat
25 the cut specimen with talc powder.

30 The film thickness of the specimen was measured at five or more locations along the length. The average film thickness was calculated to ± 0.001 mm. The thickness cannot vary by more than 0.01 mm over this length. Another specimen was taken if this condition was not met. The width of the specimen was measured at two or more locations and the average value calculated to ± 0.1 mm.

The geometry of the sample was entered into the instrument. The length field was set at a value of 23.2 mm and the measured values of width and thickness of the sample specimen were entered into the appropriate fields.

35 Before conducting the temperature sweep, moisture was removed from the test samples by subjecting the test samples to a temperature of 80°C in a nitrogen

atmosphere for 5 minutes. The temperature sweep used included cooling the test samples to about -60°C or about -80°C and increasing the temperature at about 1 /minute until the temperature reached about 60°C to about 70°C. The test frequency used was 1.0 radian/second.

5

Having described specific embodiments of the present invention, it will be understood that many modifications thereof will readily be apparent to those skilled in the art, and it is intended therefore that this invention is limited only by the spirit and scope of the following claims.

10

11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192